

i-POWER

DC POWER SYSTEM DATASHEET

9 KW - 12 KW



9 KW - 12 KW

Compact Subrack, Critical Site, More Space

This 2U DC power subrack delivers up to 9 kW - 12 kW of reliable power in a compact design — ideal for installations and critical infrastructure.

Engineered for harsh environments, it operates from -40°C to +65°C and up to 4000 meters altitude, ensuring consistent performance even in the most demanding conditions.



PRODUCT OVERVIEW

Input Distribution	
Parameter	Description
Input Mode	220 VAC Single Phase
Input Terminal	63 A x 1 PN x 1
Input Frequency	45-65 Hz, rated value : 50/60 Hz
AC SPD	None

Output Distribution	
Parameter	Description
Output Voltage	-42~-58VDC, rated value: -53.5VDC
Maximum Capacity	9 kW / 12 kW
Battery Terminal	63 A / 1 PN x 1
Load Terminal	LLVD : 10A/1P x 2 + 16A/1P x 2 +20A/ 1P x 2 + 40 A / 1P x 1
DC SPD	10 kA/8/20us

Controller	
Parameter	Description
Signal Input	2 AI (1 battery Temp, 1 Ambient Temp), 8 DI
Alarm Output	2 dry contact
Communication Port	RS485, SNMP
Display Mode	LCD

Environment	
Parameter	Description
Operating temperature	-40°C - 65°C(non-derating under 55 °C) -40 °C, can startup; 55 ~65°C,linear derating to 80%
Operating humidity	5%~95% (no condensation)
Altitude	0~4000m(If the altitude is within the range of 3000m to 4000m, the maximum operating temperature decreases by 1°C as the altitude increases by 200m.

Dimension	
Parameter	Description
H x W x D	88.9 mm x 482.6 mm x 469.2 mm
Height	2 U

Contact Us

Fahman Yusron
fahman@ipower-global.com
+62-813-1107-3752

Alvin Navies
alvin@ipower-global.com
+62-853-7656-9376

i-POWER
Empowering Connectivity Everywhere
www.ipower-global.com

POWER GLOBAL HOLDINGS LTD

RM NO. 32, BLOCK F, 9/F, MAITAK INDUSTRIAL BUILDING,
221 WAI YIP ST, KWUN TONG, HONG KONG